

## WIDOCRYL-Topsiegel SV



### **Basis**

Methyl methacrylate resin

### **Curing with hardener (at + 20°C)**

Rainproof after 30 min.

Walkable after 60 min.

### **Consumption**

Approx 500 - 700 g/m<sup>2</sup>

### **Basic colours**

Window grey, light grey, pebble grey, ivory, light ivory, beige, oxide red

### **Packaging unit**

10.00 kg, 5.00 kg

### **Min. working temperature**

-5°C

### **Temperature resistance**

-30°C to +80°C

### **Cleaning in fresh condition**

WIDOPAN-Cleaner

### **Storage**

If container is kept closed and storage temperature held constantly below +20°C, the product may be used for up to 6 months.

### **Balconies, terraces, walkways**

WIDOCRYL-Topsiegel PM is used as decorative topping on surfaces.

It may be used on waterproofings, primings and wearing layers from Widopan.

WIDOCRYL-Topsiegel SV is based on methyl methacrylate resin.

The surface to be sealed must be dry, clean and free from grease and dust.

### **Mixing**

WIDOCRYL-Topsiegel SV must be carefully stirred before adding the hardener. Because of the short working time, only fairly small amounts should be mixed with hardener.

The required amount of hardener depends on the temperature. For details see container lid.

Further details, especially regarding hazard statements, security advices and measures in the event of fire can be found in the safety data sheet under sections 2, 4, 5, 6, 7 and 8.

**Please also refer to our technical information sheets!**