



Liquid synthetic systems  
for the waterproofing of buildings

# WIDOCRYL-TEN



***Detail, penetrations and roof repairs  
-quick, reliable, permanent solutions***



Liquid synthetic systems  
for the waterproofing of buildings

## WIDOCRYL-TEN Liquid waterproofing

*Roof repairs, particularly where penetrations and openings are concerned call for a rapid and reliable detail-related solution. For it is only the waterproofing of all details which guarantees permanent waterproofing success.*

### The material

The material base of WIDOCRYL-TEN is urethane-modified methyl methacrylate resin (PMMA), which, for work on transitional features, has been made slightly thixotropic. A polyester fleece is encapsulated for reinforcement, which in turn determines elongation at rupture and breaking strength and ensures a uniform layer thickness. It is adjusted on site to the conditions of the structural shell, thus producing an homogeneous and crack-filling waterproofing which is permanently elastic.

### Possibilities of use

Detail penetrations and all kinds of roof fixtures, e.g. pipe openings, handrail supports and outlets, benefit from a reliable, long-term seal with WIDOCRYL-TEN waterproofing. WIDOCRYL-TEN will adhere to practically all bitumen, synthetic and rubber roofing sheets currently used for the waterproofing of roofs, and in most cases without any

Over 30 years of success  
in new build  
and refurbishment

prior priming. The reinforcement covering must be a minimum of 5 cm lap. Covering for any different materials must be determined on a case by case basis, but should not be less than 10 cm wide.

WIDOCRYL-Topsiegel-PM allows the material to be colour-designed and thus to be adapted to different environments.

### Rapid curing

Thanks to the addition of hardener, which will depend on temperature, WIDOCRYL-TEN will cure effectively, even at low temperatures down to - 5°C substrate temperature. The material is rain-proof after as little as 15 minutes and will have fully cured after 30 minutes.

### Approved in Europe:

WIDOCRYL-TEN is approved as a roof waterproofing material and meets the requirements of the European Construction Products Directive (CE label) and has European technical approval (ETA).





Liquid waterproofing systems for sealing buildings



WIDOPUR 1K

WIDOPUR 1K is a one-component product, which is ready-to-use straight from the container.  
WIDOPUR 1K - homogeneous and fills cracks.  
WIDOPUR 1K - reliable to use and economical in consumption.  
■ For new build, renovation and repair for permanent protection.  
■ On surfaces and for attachments and penetrations - just pour once.

**The better way of liquid waterproofing - with the liquid synthetic product WIDOPUR 1K!**

WIDOPAN-FD



The liquid waterproofing sealant for flat roofs, podiums, detail connections and jointing details

### Flüssigkunststoffe für Sanierung und Neubau

WIDOPAN Produkte GmbH  
Finkenhörne 4a  
21781 Cadenberge (Germany)  
Telefon +49 4777 8081-0  
Telefax +49 4777 8081-20  
kontakt@widopan.de  
www.widopan.de

Fugendichtung  
Flachdach  
Balkon  
Terrasse  
Laubengang  
Parkdeck  
Detail-Anschlüsse

### Liquid synthetics for renovation and new build

WIDOPAN LIMITED  
West Horndon  
CM13 3XL Brentwood, Essex  
Tel.: +44 (0)854 265 8008  
Fax.: +44 (0)854 265 8009  
www.widopan.co.uk

Joint sealing  
Flat roofs  
Balconies  
Terraces  
Arbours  
Car park floors  
Detail transitions