

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

WIDOPAN-FD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Liquid plastic sealing system, pigmented

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

Widopan Produkte GmbH
Ostereichen 3
D-21714 Hammah

Telephone no. +49 (0) 4144 69821-0

Fax no. +49 (0) 4144 69821-20

Information provided by / telephone

+49 (0) 4144 69821-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 3; H412

Eye Irrit. 2; H319

Flam. Liq. 3; H226

Repr. 2; H361

Skin Irrit. 2; H315

STOT RE 1; H372

STOT SE 3; H335

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07



GHS08

Signal word

Danger

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

Hazardous component(s) to be indicated on label:

styrene

Hazard statement(s)

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Hazard statements (EU)

EUH208	Contains COBALT BIS(2-ETHYLHEXANOATE), octabenzone. May produce an allergic reaction.
--------	---

Precautionary statement(s)

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection.
P314	Get medical advice/attention if you feel unwell.
P370+P378	In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

unsaturated polyester-elastomer in co-reactant diluent styrene, liquid

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	styrene		
	100-42-5 202-851-5 601-026-00-0 01-2119457861-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Asp. Tox. 1; H304 STOT SE 3; H335 STOT RE 1; H372 Aquatic Chronic 3; H412 Repr. 2; H361d	>= 25.00 - < 50.00 %-b.w.
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics		
	- 918-167-1 - 01-2119472146-39	Aquatic Chronic 4; H413 Asp. Tox. 1; H304 EUH066 Flam. Liq. 3; H226	< 5.00 %-b.w.
3	COBALT BIS(2-ETHYLHEXANOATE)		
	136-52-7 205-250-6 - 01-2119524678-29	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Skin Sens. 1; H317 Eye Irrit. 2; H319 Repr. 2; H361f	< 0.50 %-b.w.
4	octabenzene		
	1843-05-6 217-421-2 - 01-2119557833-30	Skin Sens. 1B; H317	< 0.50 %-b.w.
5	titanium dioxide		
	13463-67-7 236-675-5 - 01-2119489379-17	-	< 2.50 %-b.w.

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Route, target organ, concrete effect
1	H372 inhalational; ear; -

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. If the patient is likely to become unconscious, place and transport in stable sideways position.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air. Irregular breathing/no breathing: artificial respiration. Call a doctor immediately.

After skin contact

Wash off immediately with soap and water. Don't use solvents.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). Seek medical assistance.

After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Water spray jet; Carbon dioxide

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Wear protective clothing. Suppress gases/vapours/mists with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Wash hands before breaks and after work. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

Advice on storage assembly

Do not store together with: oxidizing agents

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
List of approved workplace exposure limits (WELs) / EH40			
Styrene			
	WEL short-term (15 min reference period)	1080	mg/m ³ 250 ppm
	WEL long-term (8-hr TWA reference period)	430	mg/m ³ 100 ppm
2	titanium dioxide	13463-67-7	236-675-5
List of approved workplace exposure limits (WELs) / EH40			
Titanium dioxide			
total inhalable dust			
	WEL long-term (8-hr TWA reference period)	10	mg/m ³
List of approved workplace exposure limits (WELs) / EH40			
Titanium dioxide			
respirable dust			
	WEL long-term (8-hr TWA reference period)	4	mg/m ³
3	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
List of approved workplace exposure limits (WELs) / EH40			
Cobalt compounds			
Co			
	WEL long-term (8-hr TWA reference period)	0.1	mg/m ³

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	styrene	100-42-5 202-851-5		
	dermal	Long term (chronic)	systemic	406 mg/kg/day
	inhalative	Short term (acut)	systemic	289 mg/m ³
	inhalative	Long term (chronic)	systemic	85 mg/m ³
	inhalative	Short term (acut)	local	306 mg/m ³
2	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7 205-250-6		
	inhalative	Long term (chronic)	local	235 µg/m ³

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	styrene			100-42-5 202-851-5	
	oral	Long term (chronic)	systemic	2.1	mg/kg/day
	dermal	Long term (chronic)	systemic	343	mg/kg/day
	inhalative	Long term (chronic)	systemic	10.2	mg/m ³
	inhalative	Short term (acut)	systemic	174.25	mg/m ³
	inhalative	Short term (acut)	local	182.75	mg/m ³
2	COBALT BIS(2-ETHYLHEXANOATE)			136-52-7 205-250-6	
	oral	Long term (chronic)	systemic	55	µg/kg/day
	inhalative	Long term (chronic)	local	37	µg/m ³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	styrene		100-42-5 202-851-5	
	water	fresh water	0.028	mg/L
	water	marine water	0.014	mg/L
	water	fresh water sediment	0.614	mg/kg dry weight
	water	marine water sediment	0.307	mg/kg dry weight
	water	Aqua intermittent	0.04	mg/L
	soil	-	0.2	mg/kg dry weight
	sewage treatment plant	-	5	mg/L
2	COBALT BIS(2-ETHYLHEXANOATE)		136-52-7 205-250-6	
	water	fresh water	0.6	µg/L
	water	marine water	2.36	µg/L
	water	fresh water sediment	9.5	mg/kg dry weight
	water	marine water sediment	9.5	mg/kg dry weight
	soil	-	10.9	mg/kg dry weight
	sewage treatment plant	-	0.37	mg/L

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form/Colour			
liquid			
grey			
Odour			
typical; of styrene			
Odour threshold			
No data available			
pH value			
No data available			
Boiling point / boiling range			
Value	145	- 146	°C
Reference pressure		1013	hPa
Melting point / melting range			
No data available			
Decomposition point / decomposition range			
No data available			
Flash point			
Value		31	°C
Ignition temperature			
Value		490	°C
Auto-ignition temperature			
No data available			
Oxidising properties			
No data available			
Explosive properties			
No data available			
Flammability (solid, gas)			
No data available			
Lower flammability or explosive limits			
No data available			
Upper flammability or explosive limits			
No data available			
Vapour pressure			
Value		6.24	hPa
Reference temperature		20	°C

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

Vapour density			
No data available			
Evaporation rate			
No data available			
Relative density			
No data available			
Density			
Value	1.02	g/cm ³	
Reference temperature	20	°C	
Solubility in water			
No data available			
Solubility(ies)			
No data available			
Partition coefficient: n-octanol/water			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
log Pow		2.96	
Reference temperature		25	°C
Source	ECHA		
Viscosity			
Value	750 - 1150	mPa*s	
Reference temperature	20	°C	
Solvent separation test			
Value	< 3	%	
Solvent content			
Value	appr. 37	%	

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

No data available.

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

None, if handled according to intended use.

10.5 Incompatible materials

Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products known.

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	-	918-167-1
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	OECD 402		
Source	ECHA		
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	-	918-167-1
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	OECD 402		
Source	ECHA		

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	WIDOPAN-FD
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
LC50		11.8	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Source	ECHA		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
Species	rabbit		
Source	ECHA		
Evaluation	irritant		
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	-	918-167-1
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
	Species	rabbit	
	Source	ECHA	
	Evaluation	irritant	
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	-	918-167-1
	Species	rabbit	
	Method	OECD 405	
	Source	ECHA	
	Evaluation	non-irritant	

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
	Route of exposure	Skin	
	Species	guinea pig	
	Source	ECHA	
	Evaluation	non-sensitizing	
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	-	918-167-1
	Route of exposure	Skin	
	Species	guinea pig	
	Method	OECD 406	
	Source	ECHA	
	Evaluation	non-sensitizing	

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	-	918-167-1
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are met.	
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	-	918-167-1
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	-	918-167-1
	Source	ECHA	
	Evaluation/classification	Based on available data, the classification criteria are not met.	

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

STOT - single exposure
No data available
STOT - repeated exposure
No data available
Aspiration hazard
No data available
Delayed and immediate effects as well as chronic effects from short and long-term exposure
Inhalation of vapours may lead to headache, drowsiness and dizziness. Inhalation of vapours in higher concentration may lead to irritation of eyes, nose and respiratory tract. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
LC50		4.02	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Source	ECHA		

Toxicity to fish (chronic)			
No data available			

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
EC50		4.7	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
NOEC		1.01	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
EC50		4.9	mg/l
Duration of exposure		72	h
Species	Selenastrum capricornutum		
Method	EPA OTS 797.1050		
Source	ECHA		

Toxicity to algae (chronic)			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
EC10		0.28	mg/l
Duration of exposure		96	day(s)
Species	Selenastrum capricornutum		
Method	EPA OTS 797.1050		
Source	ECHA		

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
EC50		appr. 500	mg/l
Species	activated sludge		
Method	OECD 209		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
Type	ThOD		
Value		70.9	%
Duration		28	d
Method	ISO DIS 9408		
Source	ECHA		
Evaluation	readily biodegradable		

Abiotic Degradation			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
Type	Photolysis		
Half-life		7.4	h
Source	ECHA		

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
log Pow		2.96	
Reference temperature		25	°C
Source	ECHA		

12.4 Mobility in soil

Mobility in soil			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
log Koc		2.55	
Reference temperature		20	°C
Method	QSAR		
Source	ECHA		

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	III
Hazard identification no.	30
UN number	UN1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Technical name	styrene
	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
Tunnel restriction code	D/E
Label	3
Comments	Containers with a capacity <= 450 ltrs are not subject to ADR-regulations (refer to 2.2.3.1.5.)

14.2 Transport IMDG

Class	3
Packing group	III
UN number	UN1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Technical name	styrene
	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
EmS	F-E, S-E
Label	3
Comments	Containers with a capacity <= 30 ltrs are not subjected to IMDG regulations, chapter 4.1, 5.2 and 6.1 (see IMDG-Code 2.3.2.5)

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	III
UN number	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Technical name	styrene
	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

Trade name: WIDOPAN-FD

Current version : 4.0.0, issued: 25.01.2019

Replaced version: 3.1.0, issued: 07.03.2018

Region: GB

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe XVII.	No 3, 40
---	----------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P5c
--	-----

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH066	Repeated exposure may cause skin dryness or cracking.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Department issuing safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 21803